

NEVOSOFT® JS 120

Jeans Softener

Characteristics

Modified amino functional polydimethylsiloxane emulsion.

Properties

- ✓ Yields soft and silky touch to the blue jeans
- ✓ Ensures good exhaustibility and wash resistance
- ✓ Does not cause yellowing

Application

NEVOSOFT® JS 120 is used as a softener during the piece-finishing process of blue jeans. The product is especially designed to prevent ozone fading of indigo which can cause yellowing due to its exposition to polluted air.

Technical Data

Appearance	Brown, liquid
Solid content (%)	20 (±1)
Emulsifier type	Non-ionic
pH	5,0–7,0

* These figures are only intended as a guide and should not be used in preparing specifications.

Processing

NEVOSOFT® JS 120 can be applied by padding method. The finishing liquors should not be subjected to high shear, as this might cause instability. It is important to keep controlling the bath pH between 5,0-5,5 and the bath temperature below 40°C during the process. It is recommended to use 5-30 g/l of NEVOSOFT® JS 120 for padding. It is important to remove chlorine residues from the medium before the application.

Storage / Shelf Life

NEVOSOFT® JS 120 has a shelf life up to 9 months if stored in tightly closed original containers between 5-35°C. If the material is kept beyond the shelf life recommended, it is not necessarily unusable, but quality control should be performed on the properties relevant to the application. The containers must be protected against sunlight and frost.

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants with the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials.

Editing Date: 09.11.15
Revision No/Date: -
Page: 1/1

Ultrakim Kimya San. ve Tic. A.S.
Haramidere Sanayi Sitesi M Blok
No: 322–324 Avcilar, 34840, Istanbul/Turkey
Tel: + 90 212 422 05 14
Fax: + 90 212 422 05 15
Email: info@ultrakim.com

www.ultrakim.com

NEVOSOFT® JS 120

Jeans Softener

Packaging

30, 60, 120 and 220 kgs plastic drums or 1,000 kgs IBC containers.

Technical
Data
Sheet

NEVOSOFT®

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants with the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials.

Editing Date: 09.11.15
Revision No/Date: -
Page: 2/1

Ultrakim Kimya San. ve Tic. A.S.
Haramidere Sanayi Sitesi M Blok
No: 322-324 Avcilar, 34840, Istanbul/Turkey
Tel: + 90 212 422 05 14
Fax: + 90 212 422 05 15
Email: info@ultrakim.com
www.ultrakim.com