

# NEVOSOFT® RA 1540-2 macro

## Textile Softener

### Characteristics

Non-ionic, amino functional polydimethylsiloxane emulsion.

### Properties

- ✓ Provides special slickness to the fabric
- ✓ Yields soft, filled and permanent hand
- ✓ No risk of yellowing
- ✓ Ensures excellent sewability

### Application

NEVOSOFT® RA 1540-2 macro is ideal as a permanent softener and lubricant for all kind of textile fabrics. Due to its reactive structure, it provides slippery, soft and filled elastomeric touch to the fabrics without risk of yellowing. Besides, it helps to improve the sewability of fabrics.

### Technical Data

Appearance	White liquid
Solid content (105°C–1h) (%)	40 (±1)
Emulsifier type	Non-ionic
pH	5,0–7,0

\* These figures are only intended as a guide and should not be used in preparing specifications.

### Processing

NEVOSOFT® RA 1540-2 macro can be applied by padding method. The finishing liquors should not be subjected to high shear, as this might cause instability. It is important to keep controlling the bath pH between 5,0-6,0 and the bath temperature below 40°C during the process. It is recommended to use 5-30 g/l of NEVOSOFT® RA 1540-2 macro for padding. The recommended fixing time and temperature is 1-3 min and 130–165°C, respectively.

NEVOSOFT® RA 1540-2 macro could be combined with all conventional cationic, nonionic softeners and other additives. However, the compatibility tests should be done before the application. Due to the cationic structure of its active material, NEVOSOFT® RA 1540-2 macro cannot be used together with anionic auxiliary substances.

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants with the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials.

## NEVOSOFT® RA 1540-2 macro

*Textile Softener*

### Storage / Shelf Life

NEVOSOFT® RA 1540-2 macro has a shelf life up to 9 months if stored in tightly closed original containers between 5-35°C. If the material is kept beyond the shelf life recommended, it is not necessarily unusable, but quality control should be performed on the properties relevant to the application. The containers must be protected against sunlight and frost.

### Packaging

30, 60, 120 and 220 kgs plastic drums or 1,000 kgs IBC containers.

Technical  
Data  
Sheet

NEVOSOFT®

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants with the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials.

Editing Date: 07.03.13  
Revision No/Date: 01/30.12.13  
Page: 2/2

**Ultrakim Kimya San. ve Tic. A.S.**  
Haramidere Sanayi Sitesi M Blok  
No: 322-324 Avcilar, 34840, Istanbul/Turkey  
Tel: + 90 212 422 05 14  
Fax: + 90 212 422 05 15  
Email: info@ultrakim.com  
**www.ultrakim.com**